



Virtual Machine Logbook 10/21/2008

Andrea Cavalli
Julien Poffet

Table of Contents

- Context
- Motivation
- Virtual Machine Logbook
 - Examples of use
 - Where we are
 - Further work
- Summary


Context - ATLAS

- Software development in the ATLAS experiment
 - Analysis programs are dependent on working environment
 - ► Environment = ATLAS version, compiler, OS ...
 - Different machines = different working environments
 - ▶ Same program on two different machines \neq same behavior
 - Reproduce an environment is hard
 - Sharing the work is difficult
- Idea
 - ▶ Use the benefits of virtualization → CernVM



Context – Virtual machine (VM)

- ▶ Abstraction of a real computer
 - The environment is contained into the VM
- Operations on virtual machines
 - Start
 - Stop
 - Suspend
 - Snapshot
- Isolation between VM and the host
- Easy to share → consist in a file copy/transfer





Context - CernVM

- Idea
 - Develop inside the virtual machine
- Provide virtual machines
 - Working environment (OS + specific software)
 - Used for analysis on LHC data
 - ▶ Both for development and production
- CernVM virtual machines are:
 - Configurable
 - Multi-format
 - Independent of hardware and software platform
 - ▶ Only a suitable virtual player is required (VMware, Xen...)




VML project goals

- VML = Virtual Machine Logbook
- Provide a simple backup/versioning system
- Keep the size of the backups small
- Increase the usability of CernVM virtual machine
- Simplify the sharing of work environments
- Multi-format

Structure


- Working area
 - Provide space to run the virtual machine
- Repository
 - Store the backups of the virtual machines (VML entries)




Save a virtual machine state

\$> vml.py save entry1







- You can save running virtual machines
 - Save a running VM takes more space in the repository than save a powered off VM

Consult


Print the content of the repository and of the working areas


\$> vml.py consult


```
Repositories:
                                 path
              entries
name
repl*
             ['entry|']
                                /scratch-local/poffet/vml/repl
Working Area:
                                                                                                      repi
                                                                           wal
                                 path
              entry
name
wal
             entry l
                                /scratch-local/poffet/vml/wal
                                                                      Virtual Machine
                                                                                                      entry l
Entries in repository:
+---entry1(10/16/08 - 09:51:25 - full)
```

Save a virtual machine state

\$> vml.py save entry2







- ► Entry I is a full backup
- ▶ Entry 2 is an incremental backup based on Entry I
 - Contains just the differences from Entry I → smaller size

Consult

\$> vml.py consult

```
Repositories:
             entries
                                 path
name
rep I* ['entry I', 'entry2'] /scratch-local/poffet/vml/rep I
Working Area:
                               path
name
             entry
                               /scratch-local/poffet/vml/wal
wal
            entry2
                                                                                              repí
                                                                   wal
Entries in repository:
                                                                                              entry I
+---entry1(10/16/08 - 09:51:25 - full)
                                                              Virtual Machine
 +---entry2(10/16/08 - 09:58:25 - incremental)
                                                                                              entry2
```


Open an entry in a working area

\$> vml.py open entry2





> VML builds the VM and starts it



Multiple working areas


▶ Allow to start multiple VMs at the same time






VML now: entries exchange

- Share your entries with other VML users
 - User A exports the entry
 - User B imports the entry: he can now open it (= start the VM)




Further work: CernVM integration

- Incremental entries have a common base: CernVM
 - ▶ The size of the transferred entries is small (~50 MB or less)
- Automatic CernVM virtual appliances download











VML now: VMs management

- Done through the VMware Server API
- VML works only with VMware virtual machines




Further work: platform independence

Support other virtual machines platforms (Xen, QEMU, KVM…)




Further work: environment backups

- Backup
 - ▶ Environment and relevant files copy
- Restore
 - ▶ Push the files and the environment into the virtual machine



Further work

Use VML to deploy VMs on a cloud or a cluster (like PDSF)



Summary

Motivation

- Avoid the issues raised by working on different environments
- Need to share the work (the virtual machines)

VML provides the following benefits

- Simplify the management of the virtual machines
- Keep a history of the work
- Easy way to share the work

Schedule

- This project will be delivered to ATLAS by February
- The goal is to have it distributed as a tool with CernVM



Thank you for your attention

